

ZAF109

Explosion Proof Infrared Camera



Certificate	
Certificate Mark	Exd IIC T6 Gb/ Ex tD A21 IP68 T80°C
Certificate No	CNEx16.2526
Standards	Q/320412 ZAF033-2016
Mechanical	
Housing	Stainless steel 304 or 316L
IP	IP68
Cable thread hole	1pcs G3/4 or NPT3/4
Electrical	
Voltage	DC24V or POE power supply
Power	8W
Ambient	
Ambient temperature	-25 to +60°C
Air pressure	80Kpa to 106Kpa
Relative Humidity	≦95% (no condensation)
Lights	
Light distance	20-30m
Network	
Network Interface	1pcs of RJ45, support 10M/100M/1000M
Video Compression	H.265/ H.264/ M-JPEG
Stream	Support three streams
Internet Protocol	IPv4/IPv6,HTTP,HTTPS,802.1x,Qos,FTP,SMTP,UPnP,SNMP
Time Display	Support
Standard	ONVIF, CGI, GB/T28181, PISA
IE browser	Support IE7 or above, Google, Firefox, Apple
Security	Password protection, Multiple access control
Camera	
Image Sensor	1/2.8" COMS, 1/3" COMS

Effective pixel	1.3MP, 2MP
Min. Illumination	0.01Lux @(F1.2, AGC ON) B/W: 0Lux with IR
Lens	4mm @ F2.0, view angle:85° (6mm, 8mm, 12mm)
Day& Night	Auto ICR
WDR	120dB
3D DNR	Support
BLC	ON/OFF
Image setting	Mirror, Saturation, Brightness, Contrast, Sharpness adjusta

General

Cable	integrated cable
Size	158*144*167mm
Weight	4kg
Mounted	wall, pole
Wall bracket	ZAZ109B

Dimension

