



## ZAT630

### Network Explosion Proof PTZ

### Dome Camera

#### Certificate

Certificate Mark	Exd IIC T6 Gb/Ext DA21 IP68 T80°C
Certificate No	CNEx15.2504X
Standards	Q/320412 ZAF026-2015

#### Mechanical

Housing	Stainless steel 304 or 316L
IP	IP68
Cable thread hole	1pcs G3/4 or NPT3/4
Wiper	No

#### Electrical

Voltage	AC85V~AC265V or DC24V or AC24V
Power	25W /35W (with thermostat)
Surge Protect	Optional, TVS6000V surge protect

#### Ambient

Ambient temperature	-25 to +60°C
Air pressure	80Kpa to 106Kpa
Relative Humidity	≤95% (no condensation)

#### Communication

Communication	support analog video output
485 Communication	Support Pelco-D, Pelco-P
Communicate Rate	2400 to 19200bps

#### Pan & Tilt

Horizontal	360°
Speed	Horizontal 0.1-300°/s, Vertical 0.1-250°/s
Vertical	-90 to +0
Cruise Scan	Support

Keep watch	Support
Preset	64/128/255/300
Resume function	Support
Auto Cruise	Support
Auto Pattern	Support
Auto Scan	Support

## Alarm

Alarm Input	2-channel/ 7-channel
Alarm Output	1-channel, action with alarm
Action with Alarm	Screen scratch, Preset, Pattern, Cruise, SD record, email
Intelligent Alarm	Audio detective, move detective, video shield, network inte

## Audio

Audio Input	Audio input (LINE input, MIC input), audio peak:2-2.4Vp-p,
Audio Output	Line-level impedance 600Ω

## Network

Network Interface	1pcs of RJ45, support 10M/100M/1000M
Video Compression	H.264 , H.265 / MJPEG
Audio Compression	G.711-a / G7.11mu /MP2L2/PCM
Voice Intercom	Support
Stream	Support three streams
Internet Protocol	IPv4/IPv6,HTTP,HTTPS,802.1x,Qos,FTP,SMTP,UPnP,SNMP
Time Display	Support
Standard	ONVIF, CGI, GB/T28181, PISA
IE browser	Support IE7 or above, Google, Firefox, Apple
Security	Password protection, Multiple access control

## Camera

Image Sensor	1/2.8" interline-transfer CCD
Effective pixel	1.3MP, 2MP, 3MP
Min. Illumination	Color 0.05Lux B/W: 0.01Lux
Day&night	Auto/ Color/ BW
S/N ratio	>52dB (AGC off)
Gain	off/ lower/ higher
White Balance	Auto/ Manual/ Auto tracking white balance/ indoor/outdoor/
3D DNR	Support
BLC	ON/OFF
Image setting	Mirror, Saturation, Brightness, Contrast, Sharpness adjusta

Optical zoom	20X / 30X
View Angle	Horizontal 65.5° to 2.11

## General

Cable	integrated cable
Size	213*213*570mm
Weight	15kg
Mounted	wall, pole
Wall bracket	ZAZ630B

## Dimension

