



## CZ6404

### Explosion Proof PTZ Dome Camera

#### Certificate

Certificate Mark	Ex d IIC T6 Gb/Ex tD A21 IP68 T80°C
------------------	-------------------------------------

#### Mechanical

Housing	Stainless steel 304 or 316L
IP	IP68
Cable thread hole	M27×1.25 or M25×1.5

#### Electrical

Voltage	a.c.24V/d.c.24V/d.c.12V/PoE+(d.c.48V)
Power	10W (without heating, fan)
Surge Protect	Optional, TVS6000V surge protect

#### Ambient

Ambient temperature	-40 to +60°C
Air pressure	80Kpa to 110Kpa
Relative Humidity	≦95% (no condensation)

#### Pan & Tilt

Pan/Tilt Range	Pan: 0° ~ 355°; Tilt: 0° ~ 80°
Preset Speed	Pan: 100° /s; Tilt: 60° /s
Manual Control Speed	Pan: 0.1° ~100° /s; Tilt: 0.1° ~60° /s
Preset	300

#### Camera

Image Sensor	1/3" CMOS
Effective pixel	2592(H) x 1520(V), 4 Megapixels
Min. Illumination	Color: 0.05Lux@F1.6; B/W: 0.005Lux@F1.6
Shutter Time	1/1s~1/30,000s
RAM/ROM	256M/128M
S/N Ratio	More than 50dB

#### Lens

Focal Length	2.7mm~11mm
--------------	------------

Aperture Range	F1.6 ~ F2.8
Close Focus Distance	100mm~ 1000mm

## Network

Network Interface	RJ-45 (10XBase-T/100Base-TX)
Video Compression	H.265/H.264
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICM P, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS,PP POE,DDNS,FTP, IP Filter,QoS,Bonjour,802.1x
Interoperability	ONVIF Profile S&G, API
Streaming Method	Unicast / Multicast

## General

Cable	integrated cable
Size	φ156mm×134mm
Weight	6.5KG
Mounted	wall, pole
Wall bracket	ZAZ630-B、ZAZ630-D

## Dimension

