

KBA24(A) Coal Mining Explosion Proof PTZ Camera



Certificate

Certificate Mark	ExdI
Certificate No	CCCMT12.0170
MA No	MAK120053
Standards	MT209-90 GB3836-2010 Q/320412ZAF037-2012

Mechanical

Housing	Stainless steel 304
Weight	20kg
Cable thread hole	1 pcs G3/4 or NPT3/4
Overall dimension	375*245*220mm
Mounted	wall, pole

Electrical

Voltage	AC127V, 50Hz
Input supply	$\cong 100VA$
Communication signal	RS485, Baud rate:2400
Protocol	Pelco-D, or other optional
Rotation speed	vertical $15 \pm 3' / S$, horizontal: $15 \pm 3' / S$, adjustable
Rotation angle	vertical: $0 \sim 180^\circ \pm 10^\circ$, horizontal: $0 \sim 360^\circ$ continuous
Cold light	30m
Cable	Integrated cable with power, video, control

Ambient

Ambient temperature	0 to +40°C
Air pressure	80Kpa to 106Kpa

Relative Humidity	≦ 95% (no condensation)
-------------------	-------------------------

Analog Camera

Image Sensor	1/3" interline-transfer CCD
Effective pixel	PAL 976*582 NTSC 976*494
Min. Illumination	Color 0.04Lux B/W: 0.004Lux
Shutter Time	1/50(1/60) sec~ 1/10,000 sec
Day&Night	Auto ICR
Horizontal resolution	700TVL (color), 720TVL (B&W)
S/N ratio	>50dB (AGC off)

Dimension

