

ZAZN04**Crane Damping CCTV Camera****Mechanical**

Housing	Stainless steel 304 or 316L
IP	IP68
Cable thread hole	2pcs G3/4 or NPT3/4
Stable type	oil pressured type
Impact speed	5m/s
Swing angle	$\leq 2.5^\circ$
Return back time	$\leq 1.5s$

Electrical

Voltage	AC100-240V, AC24V or POE
---------	--------------------------

Power	8W
Ambient	
Ambient temperature	-25 to +60℃
Air pressure	80Kpa to 106Kpa
Relative Humidity	≦95% (no condensation)
Network	
Network Interface	1pcs of RJ45, support 10M/100M/1000M
Video Compression	H.264 main profile / MJPEG
Audio Compression	G.722.1/ G.711-a law/ G7.11-u law/MP2L2/G.726
Voice Intercom	Support
Stream	Support three streams
Internet Protocol	IPv4/IPv6,HTTP,HTTPS,802.1x,Qos,FTP,SMTP,UPn
Time Display	Support
Standard	ONVIF, CGI, GB/T28181, PISA
IE browser	Support IE7 or above, Google, Firefox, Apple
Security	Password protection, Multiple access control
Network Camera	
Image Sensor	1/2.8" interline-transfer CCD
Effective pixel	1.3MP, 2MP,
Lens	4.7-94mm (20X), 4.5-135mm (30X)
Min. Illumination	Color 0.05Lux B/W: 0.01Lux
Day&night	Auto/ Color/ BW
S/N ratio	>52dB (AGC off)
Gain	off/ lower/ higher
White Balance	Auto/ Manual/ Auto tracking white balance/ indoor
3D DNR	Support
BLC	ON/OFF
Image setting	Mirror, Saturation, Brightness, Contrast, Sharpnes
Optical zoom	20X / 30X
General	
Cable	integrated cable
Size	526*200*249.6mm
Weight	25.9kg
Mount	On crane

Dimension

